

Key Features

- HD Voice
- 2.8" Color LCD
- 8 Line Display
- DSS Keys



Yealink SIP-T20P9L is a high-quality IP phone designed for entry-level users. It features a 2.8-inch color LCD screen that displays call information, including the caller ID and time. The phone is equipped with a standard 12-button keypad and a navigation pad for easy access to various functions. It also includes several function buttons such as MESSAGE, HEADSET, TRAN, and RD. The phone is designed for high-quality audio, featuring HD Voice technology. It is compatible with a wide range of IP networks and is easy to set up and use.

Phone Features

2 VoIP accounts, hotline, emergency call
 Call waiting, call transfer, call forward
 Hold, mute, flash, auto-answer, redial
 3-way conference, DND, speed dial
 XML phonebook import/export, call history
 Volume adjustment, ring tone selection
 Tone scheme, System log
 Multi-language (more than 20)

IP PBX System Integration

Dial plan, dial-now
 Voicemail, MWI
 Intercom
 Call park, call pickup
 Distinctive ringtone

Codecs and Voice Features

Wideband codec: G.722
 Narrowband codec: G.711, G.723.1,
 G.726, G.729AB
 VAD, CNG, AEC, PLC, AJB, AGC
 Full-duplex speakerphone with AEC

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
 NAT Traversal: STUN mode
 DTMF: In-Band, RFC2833, SIP Info
 Proxy mode and peer-to-peer SIP link mode
 IP Assignment: Static/DHCP/PPPoE
 TFTP/DHCP/PPPoE client
 Telnet/HTTP/HTTPS server
 DNS client
 NAT/DHCP server

Management

FTP/TFTP/HTTP/PnP auto-provision
 Configuration: browser/phone/auto-provision
 Direct IP call without SIP proxy
 Dial number via SIP server
 Dial URL via SIP server

Security

HTTPS (server/client)
 SRTP (RFC3711)
 Transport Layer Security (TLS)
 VLAN (802.1 pq), QoS
 Digest authentication using MD5/MD5-sess
 Secure configuration file via AES encryption
 Phone lock for personal privacy protection
 Admin/user configuration mode

Physical Features

TI TITAN Chipset
 3-line LCD with an icon line
 and 2x15 characters lines
 31 keys including 9 function keys
 4 LEDs: 1xpower, 2xline, 1xmessage
 1xRJ9 handset port
 1xRJ9 headset port
 2xRJ45 10/100M Ethernet ports
 Wall-mounted
 Power adapter: AC 100~240V input
 and DC 5V/1.2A Output (SIP-T20)
 IEEE 802.3af PoE (SIP-T2PEX)
 Power consumption: 1.4~2.6W
 Net weight: 0.77kg
 Dimension: 185x200x90mm
 Operating humidity: 10~95%
 Storage temperature: up to 60°C

Package Features

Qty/CTN: 10 PCS
 N.W/CTN: 22.86KG
 G.W/CTN: 25.26KG
 Measurement: 0.073CMB
 Carton Meas: 565x550x235MM

Certifications

